




WESTERN MOTORSPORTS

Ford Performance since 1989

2015+ F150 Ecoboost Single valve catch can




223114 Range Rd 285, Rocky View, Alberta, Canada T1X 0J7

Phone: (403) 243-6205 Fax: (403) 243-8102 www.wmsracing.com

2015+ F150 Ecoboost 3.5 & 2.7 Catch Can Install

- Assemble Catch Can to bracket with logo facing out as shown, using provided allen head screws and washers
- Remove the stock airbox as one unit (upper, lower and intake duct) to access the frame rail.
- Remove stock intake cover.

Mount Catch Can to existing round hole in drivers side frame rail as shown. Use provided bolt and locknut. The top of the bracket will line up with the top of the frame rail in the correct location.



- Attach hoses to catch can as shown on tags. Route towards passengers side under the throttle body and to the valvecover.
- Remove stock valvecover to intake plastic line.
- Plug in new hoses to valvecover and intake manifold.

Hose routing under throttle body

Hose to intake manifold

Hose to valvecover



- The drain hose can be routed out the bottom of the truck to make for easier draining of the main catch can.
- Re-install stock airbox and intake cover.

Generally draining the catch cans every oil change is sufficient but each application is different. Do not let the cans fill with oil / vapor fluid as it could cause engine damage. Draining more often in cold climates is required so the fluid does not freeze in the can. Discard any drained fluid